



PRODUCT DESCRIPTION

The Mobile Light Box system powered by SEGO seamlessly integrates cutting-edge technology with user-friendly design. Boasting a toolless assembly down to its foundation, Mobile Light Box is crafted to enhance your display experience. Magnetic electrical connectors illuminate the pre-installed UL certified LED lights within the profiles, ensuring a sleek appearance with concealed wires. The aluminum frame supports edge-to-edge customizable SEG backlit fabric graphics on both the front and back. Beyond its visual appeal, Mobile Light Box is portable, modular, and highly coveted, setting it apart from other lightboxes. Every detail has been meticulously considered, right down to the durable foam-cut carry bag, which is uniquely designed to safeguard and organize all components.

DISPLAY DIMENSIONS MLB BATTERY 85 x 200 cm (33.46" x 78.74")

DISPLAY CONSTRUCTION

Aluminum extrusion frame with plastic components

GRAPHIC MATERIAL

Dye Sub Backlit Fabric

GRAPHIC FINISHING

Silicone beading sewn onto edge of graphic

SHIPPING WEIGHTS & DIMENSIONS

85 x 200 BATTERY

49 x 14 x 8 45 x 19 x 6 30.0 lbs. 28.0 lbs.

LED LIGHT SPECIFICATION

LUMENS

BRAND	Osram	VOLTAGE (V)	24
POWER	3W	POWER (W)	42
CCT (COLOR TEMP)	6800k	LM/W	130
AVERAGE BEAM ANGEL	20°	TOTAL LM	5460
LM/W	130	AVG LM	5850
AVG LM/M ²	4800-5800	CU	.8
VOLTAGE INPUT	24V	EAV	4680

TRANSFORMER SPECIFICATION

POWER RATE
TRANSFORMER

CERTIFICATES
UL, CE, GEM
VOLTAGE INPUT
100-240V
VOLTAGE OUTPUT
25.2V
BATTERY RUNTIME
11 – 12 HRS



TOOL FREE CONNECTION



MAGNETIC WIRE CONNECTION



CLEAN CABLE MANAGEMENT



TOOL FREE FOOT CONNECTION

PARTS LIST




(qty 2) Horizontal Profile





(qty 2) Vertical Profile Top




(qty 2) Vertical Profile Bottom









SET UP INSTRUCTIONS



